Moving 55BT













MORE INFO


CHARACTERISTICS

• Very compact floor scrubber dryer suitable to work for the maintenance cleaning of limited-size areas • Ideal for cleaning car shops, sales points, gym, health care • Control panel with operator presence safety system • Low level battery indicator with brush/vacuum and traction progressive cut off • Solution water filter and solenoid valve • Easy access to the battery compartment • Quick drain and easily inspectable recovery tank • Non-marking wheels • Roto-molded polyethylene tanks, shock and acid resistant • Shock and acid resistant • The lower tank is also battery compartment • Low noise operation thanks to the protected positioning of vacuum motor. • Separate chemist. • Possibility to mount Li-ion batteries • Accessory storage facility on request • Detergent dosing kit 1,5 l only code 37033-00008 • New fulcrum and new lever for squeegee adjustment • New detergent solution adjustment level • New control panel with electrical board with Fleet Managemet System (available on request) • Sturdy aluminium brush plate with brush coupling and release

TECHNICAL DATA

	Moving 55BT	Moving 55BT	Moving 55BT	Moving 55BT
code	37033-00001	37033-00006	37033-00007	37033-00008
power supply	24 V	24 V (battery charger included)	24 V (battery and charger included)	24 V (battery and charger included)
scrubbing/squeegee width	550/800 mm	550/800 mm	550/800 mm	550/800 mm
max working capacity	2200 m²/h	2200 m²/h	2200 m²/h	2200 m²/h
solution tank capacity	55 l/14,5 gal	55 l/14,5 gal	55 l/14,5 gal	55 l/14,5 gal
recovery tank capacity	60 l/16 gal	60 l/16 gal	60 l/16 gal	60 l/16 gal
traction/traction motor	automatic/180W	automatic/180W	automatic/180W	automatic/180W
RPM/pressure on the brush	150/22 kg/48 lbs	150/22 kg/48 lbs	150/22 kg/48 lbs	150/22 kg/48 lbs
brush motor power	550W	550W	550W	550W
detergent solution system	solenoid valve	solenoid valve	solenoid valve	solenoid valve + dosing kit
depression/vacuum motor	1280 mmH_2O/400W	1280 mmH_2O/400W	1280 mmH_2O/400W	1280 mmH_2O/400W
dimension (cm)/weight	127x65x102/83 kg	127x65x102/84 kg	127x65x102/139 kg	127x65x102/139 kg

PLUS



Front-wheel drive equipped with reverse



Large and easily inspectable roto-molded polyethylene tank, shock and acid resistant



Solution tank level indicator



Chemical dispenser tank (optional)



Upgrade battery model to *Li-ion battery model*

• 1x 00055-00088 Li-ion battery 55 Ah • 1x 00056-00093 Battery charger CBH2D 24V 20A • 2x 00078-00231 Strip dual lock • 1x 00058-03383 electric extension cable for battery to battery charger connection 8 m • 1x 10002-09736 ballast

STANDARD EQUIPMENT

 • 10002-14574 PP brush Ø 533 mm - 21"	 • 00005-02282 Rear squeegee blade L.900 mm Shore 40 Th. 3 mm • 00005-02283 Front squeegee blade L.860 mm Shore 33 Th. 2 mm	 • 00056-00062 On-board Battery charger 24V 10A only for model code: 37033-00006/37033-00007/37033-00008)	 • 2 x 00055-00151 Maintenance free battery 12V 75Ah BT DC 5.5 only for model code: 37033-00007/37033-00008	

OPTIONAL

 • 2 x 00055-00149 Tubular battery Pb-acid 12V 118Ah C5	 • 2 x 00055-00130 GEL Battery 12 MFP 105 12V 105Ah C5	 • 2x 00055-00088 Battery Li-ion 25,6V 55Ah 1382Wh	 • 1x 00056-00093 battery charger 24V 20A	 • 00005-02284 Polyurethane rear blade L.900 TH. 3 • 00005-02285 Polyurethane front blade L.860 TH. 2
 • 10002-14572 Tynex brush Ø 533 mm-21" • 10002-14571 PP 03 brush Ø 533 mm-21" • 10002-14573 PES brush Ø 533 mm-21"	 • 10002-14570 EWU pad driver Ø 505 mm-20"	• 10002-08154 Perforated cap with refill hose	 • 10001-12852 accessory hook kit	