Maine HR



MORE INFO


CHARACTERISTICS

• Three steel pistons, brass axial pump head with built-in by-pass valve. • Double water seal • Total Stop. • Suction and delivery Stainless steel valves. • Integrated detergent suction with external suction probe. • Power cable holder. • Hose reel in pressure with h.p. hose 8m included. • Accessory holder. • Ergonomic handle. • Hose reel in pressure • Full assembled

TECHNICAL DATA

	Maine HR 1409 XP
code	36091-00016
rated/max pressure	140/180 bar - 2030/2610 psi
max delivery flow rate	540 l/h - 2.4 gpm
abs. power/supply	2800 W/230V 1~50Hz
motor power	2,0 kW
pump model	MPBX1/2800 rpm
T max water inlet	40°C
dimension (cm)/weight	39x39x95/26 Kg (57 lbs)

PLUS



Axial motor pump with stainless steel pistons, brass head, double water seal



Practical hose reel connected under pressure to use only the necessary length of hose and to rewind it easily after use



Convenient and functional rotary switch for easy switching on and off



Folding handle to reduce dimensions and to facilitate movement. If fully extended it makes it possible to pull the product on the rear wheels

STANDARD EQUIPMENT

 • 00080-02541 Gun M22	 • 00080-02804 Lance M22 high/ low pressure	 • 00080-02322 High pressure hose 10 m		

OPTIONAL

• 00080-02957 Sandblasting lance	• 00080-02981 Turbo lance			