Thermic 2W Lite 13L



MORE INFO

CHARACTERISTICS

• Loncin G390F gasoline engine • Axial pump with 3 ceramic pistons, brass head and integrated regulating valve • Low pressure detergent suction • Easily inspectable suction water filter • Oil-Alert safety device (lack of oil) for motor protection • Pressure gauge • Thermostatic valve for overtemperature • Ø 260 pneumatic wheels • Heavy semi-professional use

TECHNICAL DATA

	Thermic 2W lite 13L
code	36001-00052
rated/max pressure	290/310 bar - 4206/4496 psi
max delivery flow rate	900 l/h - 3.9 gpm
engine type	Loncin G390F
motor power	13 hp
pump model	CL4.5/3400 rpm
T max water inlet	60°C
dimension (cm)/weight	55x67x89/35 Kg (77 lbs)

PLUS



Linear pump with three ceramic pistons, brass head and regulating valve



Pneumatic wheels to dampen vibrations and to promote movement on any type of surface



Pressure regulating valve to vary the power of the water jet according to actual requirements



Painted steel handle with hose holder, removable during transportation

STANDARD EQUIPMENT

 • 00080-01695 Gun M22	 • 10002-04732 Lance M22 high/ low pressure	 • 10002-03703 Lancia Turbo 350 bar	 • 00080-00350 Ceramic nozzle 15° 035	 • 00014-00514 High pressure hose R2 10 m