Thermic 2W Lite 6L

T.V Thermal Valve



MORE INFO

CHARACTERISTICS

• Loncin G200F gasoline engine • Axial pump with three stainless steel pistons, brass head and integrated regulating valve with double seal • Low pressure detergent suction • Easily inspectable suction water filter • Thermostatic valve for overtemperature • Ø 260 pneumatic wheels • Heavy semi-professional use • Inflated wheels (air chamber)

TECHNICAL DATA

	Thermic 2W lite 6L
code	36001-00053
rated/max pressure	200/220 bar - 2900/3190 psi
max delivery flow rate	630 l/h - 2.7 gpm
engine type	Loncin G200F
motor power	6,5 hp
pump model	TPBH2/3400 rpm
T max water inlet	40°C
dimension (cm)/weight	55x67x80/28 Kg (61,7 lbs)

PLUS



Axial pump with stainless steel pistons, brass head, double water seal



Sturdy painted steel frame with rear inner tube wheels and front anti-vibration foot for stable positioning, handle with ergonomic handle for easy movement on any type of surface



Pressure regulating valve to vary the power of the water jet according to actual requirements



Painted steel handle with hose holder, removable during transportation

STANDARD EQUIPMENT

 • 00080-01137 Gun M22	 • 10002-03541 Lance M22 high/low pressure	 • 10002-04760 Turbo lance	 • 00080-00350 Ceramic nozzle 15° 035	 • 36001-00053 High pressure hose R1 10 m