Thermic 6,5



T.V Thermal Valve

CRANKSHAFT

GASOLINE

MORE INFO

CHARACTERISTICS

• Three ceramic coated pistons, brass linear pump head with built-in by-pass valve. • Suction and delivery stainless steel valves. • Manual start • 6.5 hp unleaded gasoline engine. • Integrated detergent suction with external suction probe. • Glicerine pressure gauge. • Hose-reel **(optional)**. • Suction hose with check valve **(optional)**. • Steel frame. • Hose holder. • Nozzles holder. • 3,1 l gasoline tank.

TECHNICAL DATA

	Thermic 6,5
code	36113-00027
rated/max pressure	180/210 bar - 2610/3045 psi
max delivery flow rate	690 l/h - 2.77 gpm
engine type	Lifan
motor power	6,5 hp
pump model	MP4/3400 rpm
T max water inlet	40°C
dimension (cm)/weight	47x57x57/38,5 Kg (84,9 lbs)

PLUS



Linear self-priming pump with three ceramic pistons and brass head



Sturdy painted steel frame with rear wheels and anti-vibration front foot for stable positioning, handle with ergonomic handle for easy movement on any type of surface



Side support for lance and gun housing



Pneumatic wheels to dampen vibrations and to promote movement on any type of surface

STANDARD EQUIPMENT

 • 00080-02517 Gun M22 - 1/4"	 • 00080-02770 Lance M22 with nozzle-holder.	 • 10002-12432 High pressure nozzle set	 • 00080-02367 High pressure hose 10 m	 • 00014-01565 Garden hose 2,5 m

OPTIONAL

• 10001-10200 High-pressure hose reel (hose not included)	 • 10002-12275 Suction hose with check valve	• 00080-02264 10 m High pressure hose - 3/8" - Ø 3/8" R2	• 00080-02261 20 m High pressure hose - 3/8" - Ø 5/16" - 400 bar	