Tucson XL



T.S Total Stop 24V

CRANKSHAFT

RPM 1400

MORE INFO

CHARACTERISTICS

• 4 poles electrical motor (1400 rpm) with thermal protection and water cooling. • Three full ceramic pistons, brass linear pump head with by-pass valve. • Low voltage and delayed Total Stop. • Suction and delivery Stainless steel valves. • Detergent built-in tank for indirect suction (2,8 lt.). • Pressure regulator. • Glicerine pressure gauge. • Hose-reel.

TECHNICAL DATA

	Tucson XL 2015 LP	Tucson XL 2021 LP	Tucson XL 2515 LP
code	36090-00001	36090-00002	36090-00003
rated/max pressure	200/230 bar - 2900/3335 psi	200/230 bar - 2900/3335 psi	250/280 bar - 3600/4061 psi
max delivery flow rate	900 l/h - 3.96 gpm	1260 l/h - 5.55 gpm	900 l/h - 3.96 gpm
abs. power/supply	7000 W/400V 3~50Hz	9400 W/400V 3~50Hz	9400 W/400V 3~50Hz
motor power	5,5 kW	7,5 kW	7,5 kW
pump model	CL6/1400 rpm	CL6/1400 rpm	CL6/1400 rpm
T max water inlet	60°C	60°C	60°C
dimension (cm)/weight	61x40x91/69 Kg (152 lbs)	61x40x91/70 Kg (154 lbs)	61x40x91/70 Kg (154 lbs)

PLUS



New CL 6.0 self-priming pump with three pistons in integral ceramic, tapered roller bearings, double oil viewer and brass head



New flanged pressure regulating valve L3.1, internal passages resized to ensure correct operation even in high operating flow conditions



Total stop delayed and in low voltage: the device delays the shutdown of the high pressure cleaner by 15 seconds from the last release of the gun lever, for safety, energy saving and prevention of faults or overheating of the motor pump.



Integrated cleaning tank with a capacity of 2.8 litres for indirect suction of the chemical product

STANDARD EQUIPMENT

 • 00080-01695 Gun M22 - 3/8 with rotating coupling	 • 00080-01724 Lance M22 high/low pressure	 • 00080-03188 Nozzle type 045 (mod. 2015) • 00080-03193 Nozzle type 070 (mod. 2021) • 00080-03187 Nozzle type 040 (mod. 2515)	 • 00080-02259 High pressure hose 10 m	

OPTIONAL

• 00080-03481 Turbo nozzle head	• High pressure hose code: 00080-02258 10 m - 310 bar 00080-02261 20 m - 400 bar 00080-02262 20 m - 400 bar 00080-02263 10 m - 400 bar food industry	• Turbo Lance code: 00080-02966 - (mod. 2015/2515) 00080-02968 - (mod. 2021)	• Sand-blasting lance code: 00080-02957 (mod. 2015/2515) 00080-02959 (mod. 2021)	