# GV 5 T Plus/GV 8 T Plus

NO-STOP REFILLING




MORE INFO

## CHARACTERISTICS

• Built-in AISI 304 stainless steel • Pivoting wheels with brakes, suitable for use in food processing areas • The boiler can be refilled from the tank provided (continuous duty) • Discharge valve • Pressure gauge • Device for using chemicals and detergents mixed with steam • Heating and activation time required: 6 min. • Control with low tension controls • Control panel: ON-OFF main switch, indicator lamp, • Satured steam at 9 bar at a temperature of 175°C.

## TECHNICAL DATA

| | GV 5 T PLUS | GV 8 T PLUS |
|---|---|---|
| code | 45010-00006 | 45010-00001 |
| max steam pressure/temperature | 9 bar/175° C | 9 bar/175° C |
| boiler absorbed power | 5000 W/380-400V ~ 50/60Hz (Ph 3) | 8000 W/380-400V ~ 50/60Hz (Ph 3) |
| steam production | 8 kg/h | 13,50 kg/h |
| boiler type/volume | Inox AISI 304/4,6 l | Inox AISI 304/4,6 l |
| water tank/detergent tank capacity | 10 l/5 l | 10 l/5 l |
| dimension (cm)/weight | 62,5x37,5x86/32 kg | 62,5x37,5x86/32 kg |

## PLUS



Simple and intuitive control panel, quick-coupling steam gun, main ON/OFF switch with lamp, boiler resistance activation lamp, steam flow rate regulator, steam ready indicator lamp, steam pressure gauge.



Unlimited autonomy thanks to the continuous power supply of the boiler, which enables water top-ups in the tank without having to stop the machine or interrupt work, with major time saving in the operating phase. Boiler with saturated steam at 9 bar at a temperature of 175°C. Equipped with 2 pumps: boiler and detergent.



Maximum safety thanks to the 1 safety thermostat, 1 pressure switch and 1 mechanical maximum pressure valve.
Discharge valve for complete discharge of the boiler; it eliminates water residues and formation of lime scale, thus lengthening the lifespan of the boiler.



Equipped with 4 pivoting wheels suitable for food environments.

## STANDARD EQUIPMENT

| | | | | |
|---|---|---|---|---|
|  • 00080-02898 Hose 3,5 m |  • 00080-02900 |  • 00080-02899 |  • 00080-02901 |  • 10001-09741 |
|  • 00080-02883 |  • 00080-02893 | • 00080-03601 Steam nozzle | | |

## OPTIONAL

| | | | | |
|---|---|---|---|---|
| • 00080-02904 Steam gun with hose (6 m) | • 00080-02903 Steam gun with hose (10 m) | • 00080-02908 Straight lance mm 750 without nozzle | • 00080-02910 Extension 650 mm | • 00080-02912 Lance with flat nozzle |
| • 00080-04383 Brass bristles brush Ø 80 | • 00080-02922 Lance for barrel | | | |