Domus IF





MORE INFO

CHARACTERISTICS

• 2 silenced two stage motor. • Suction system with by-pass cooling. • Stainless steel tank. • Professional closing hooks. • Static electric shock inhibitor. • Drain hose system. • Shock proof trolley. • Liquid float valve. • Cloth filter. • 10 m power cable. • Easy standing head (during filter cleaning). • Traceless wheels. • Accessories Ø 40.

TECHNICAL DATA

	Domus IF
code	40005-00023
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	2 - 2000 (2400) W silenced two stage motor
column depression	22 kPa/2240 mmH_2O
air suction	108 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension (cm)/weight	62x51x85/28 kg

PLUS



Anti-tipping head support, very useful while filter cleaning or when opening the tank for emptying



Anti-corrosion stainless steel tank and liquid float valve for liquid suction



Drain hose system for tank easy emptying



Shock proof trolley with two front pivoting wheels and two big rear wheels for better stability and easy movement

STANDARD EQUIPMENT

 • 00080-03979 Hose 2,5 m	 • 10001-09446	 • 00080-01931	 • 00080-01932	 • 00080-01956
 • 00080-01957	 • 00080-01958	 • 00070-00679 Cloth filter		

OPTIONAL

• 10001-08169 Paper collector filter set (10 pcs)	• 10001-09545 Cloth filter for fine dust	• 10001-08208 Nylon filter	• 10001-08168 Washable filter	• 10001-08178 Hepa filter