Windy 265 PF









MORE INFO

CHARACTERISTICS

• 2 high efficiency by pass motors. • Suction system with by-pass cooling. • Filter cleaning system. • Plastic tank (PP). • Shock proof trolley. • Liquid float valve. • Cloth filter. • 7,5 m power cable. • Traceless wheels. • Accessories Ø 40. • Handy accessory holder. • Pneumatic filter shaker

TECHNICAL DATA

	Windy 265 PF
code	40018-00005
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	2 - 2000 (2400) W
column depression	22 kPa/2200 mmH_2O
air suction	130 l/s
total volume/dust/liquid	65 l./30 l./40 l.
dimension (cm)/weight	44x46x96/13 kg

PLUS



2 high efficiency motors, suction system with by-pass cooling, rotating ON/OFF main switch



Pneumatic filter shaker and flow reverse for perfect filter cleaning for top vacuum performances



Shock proof plastic tank and liquid float valve for liquid suction, swivel connection avoiding tangles in the flex hose



Shock proof trolley with pivoting wheels for easy movement and base with accessory storage facility (accessories d. 40 mm)

STANDARD EQUIPMENT

 • 00080-03979 Hose 2,5 m	 • 10001-09446	 • 00080-01931	 • 00080-01932	 • 00080-01956
 • 00080-01957	 • 00080-01958	 • 10001-09468 Cloth filter		

OPTIONAL

• 10001-08169 Paper collector filter set (10 pcs)	• 00070-00673 Cloth filter for fine dust	• 10001-08208 Nylon filter		