


THERMIC 13 BSF

VANGUARD
versions V400



15/20 mt hose reel kit (on request)
*Kit avvolgitubo con tubo 15/20 mt
(su richiesta)*



RPM decelerator kit
Kit deceleratore di giri motore



General Features • Caratteristiche Generali

- Sturdy tubular frame with stainless steel covers
- ø 260 mm 4 pneumatic wheels
- No engine-oil safety device (oil-alert)
- Automatic decelerator to reduce the number of RPM during bypass mode
- Gearbox (with 1560 rpm pump)
- Pump with 3 integral ceramic pistons and brass pump head
- Water suction from external tank option (self-priming pumps)
- Readily serviceable self-cleaning suction water filter
- Ejector kit with regulated low-pressure detergent suction
- Overheating thermostatic valve
- Robusto telaio tubolare con carene inox
- 4 ruote pneumatiche ø 260 mm
- Dispositivo di Sicurezza mancanza olio motore
- Deceleratore automatico per la riduzione del numero di giri in fase di by-pass
- Riduttore di giri (con pompa a 1560 rpm)
- Pompa con 3 pistoni in ceramica integrale con testata in ottone
- Possibilità di aspirare acqua da serbatoio esterno (pompe autoadescanti)
- Filtro acqua aspirazione autopulente facilmente ispezionabile
- Kit eiettore con regolazione aspirazione del detergente in bassa pressione
- Valvola termostatica di protezione da sovratemperatura
- Uso professionale intensivo

Technical Features • Caratteristiche Tecniche

CODE CODICE	MODELS MODELLI	PUMP POMPA	MAX		WORK		I/h	HP kW		kg	(L x W x H) cm
			bar	MPa	bar	MPa					
8.601.0222	Thermic 13 BSF 2518	CL5	260	26	30±24,5	3±24,5	340±1080	14	10,4	72	95 x 68 x 95 95 x 68 x 55 *

* Height with folding handle closed - Altezza con manubrio regolabile chiuso

Standard Equipment • Dotazione Standard



GH 301 gun with swivel
Pistola GH 301 con swivel



10 m rubber delivery hose kit
Kit tubo gomma mandata 10m



Bent lance with detergent head, without nozzle
Lancia angolata con testina detergente, senza ugello



Fan shape nozzle, 1/4" MEG connection
Ugello con getto a lama attacco 1/4" MEG